

NATIONAL SEEDS CORPORATION LTD
681-690, MARKET YARD, GULTEKDI, PUNE

No.8(3)/NSC:PNA/ENGG/2014-15

Date:18.06.2014

CORREGENDUM

Refer NIT published on 17.06.2014 of our website www.indiaseeds.com for providing vitrified tiles and painting for the portion occupied by the Regional Office, Pune, there was no schedule of quantities attached. Now schedule of quantities is attached below and this is treated as part of NIT published on 17.06.2014.

Regional Manager
NSC, Pune

NATIONAL SEEDS CORPORATION LTD, PUNE

SCHEDULE OF QUANTITY

Providing vitrified tiles and painting for the portion occupied by the Regional Office, Pune

S.No	Item of works	Quantity	unit	Rate	Amount	Remarks
1	Providing and laying vitrified floor tiles in different sizes (thickness to be specidied by the manufacturer) with water absorption's less 0.08% and conforming to IS:15622 of approved make in all colours and shades, laid on 20mm thick cement mortar 1:4 (1 cement : 4 coarse sand) including grouting the joints with white cement and matching pigments etc., complete					
	Size of Tiles 60x60cm	231.35	sqm			
2	Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quuick-set tile adhesive (water based) conforming to IS: 15477, using 5kg adhesive per sqm of tile area, in average 3mm thickness	231.35	sqm			
3	Providing and laying vitrified floor tiles in different sizes (thickness to be specidied by the manufacturer) with water absorption's less 0.08% and conforming to IS:15622 of approved make in all colours and shades, in skirting, riser of steps, over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand), including grouting the joint with white cement & matching pigment etc. complete. laid on 20mm thick cement mortar 1:4					
	Size of tiles 600x600mm	10.71	sqm			
4	Removing white or colour wash by scrapping and sand papering and preparing the surface smooth including necessary repairs to scratches etc. complete	823.63	sqm			
5	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade:					
	Old work (one or more coats)	823.63	sqm			
6	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade:					
	One or more coats on old work	174.47	sqm			
7	12 mm thick plaster of mix 1:6 (1cement: 6 coarse sand)	50	sqm			
8	Dismantling of old plaster or skirting raking out joints and cleaning the surface for plaster including disposal of rubbish to the dumping ground within 50m lead.	650	sqm			

